

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Россия (495)268-04-70

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Казахстан (772)734-952-31

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

www.2mag.nt-rt.ru | | mge@nt-rt.ru

Технические характеристики на мульти-позиционные мешалки с внешним блоком управления MIXdrive 6 КОМПАНИИ **2mag**

MIXdrive 6

Ultra flat, wear-free 2mag magnetic stirrer with 6 stirring positions, suitable for 6 x 1,000 ml Erlenmeyer flasks, stirring point distance 130 mm.



6 stirring positions, 100% maintenance-free and wear-free by inductive 2mag-Magnetic-Drive concept for powerful mixing of solutions, power reserves up to 3,000 ml per stirring point, 100% synchronized speeds, jerk-free stirring even at low speeds. Fully encapsulated and hermetically sealed stainless steel housing, IP68, water-, dust-, and germproof, extremely robust construction and performance, easy to clean and maximum resistance, submersible in water- resp. oil baths, suitable for the use in CO₂-incubators and ovens.

Two different temperature areas available:

Basic-version up to +50 °C, **HT-version** up to +95 °C submerged in water baths and up to +200 °C in ovens, individual dimensions on request.

- Wear-free magnetic stirrer, up to +200°C
- Submersible, up to +95 °C
- Stirring speed from 100 up to 2,000 rpm (depending on the control unit)
- 6 stirring positions
- Stirring point distance 130 mm
- Extremely robust construction
- Integrable in systems
- 3 years warranty
- Developed and made in Germany

Please order control unit separately.

Technical data	Equipment comparison
Type	MIXdrive 6
Stirring points	6
Stirring point distance	130 mm
Stirring volume / stirring point	1 - 3,000 ml
Stirring power (max.)	40 W
Material housing	Stainless steel
Permitted operation conditions Basic-version	-10 up to +50 °C in air, up to +50 °C in water submerged
Permitted operation conditions HT-version	up to +200 °C in air, up to +95 °C in water submerged
Operating voltage (max.)	48 VDC
Dimensions (WxDxH)	245 x 375 x 38 mm
Protection category	IP68
Weight (gross)	approx. 9.4 kg

Order no. Basic-version	40006
Order no. HT-version	40206

Individual units and dimensions on request.
 3 years warranty on material and manufacturing.
 We reserve the right to make technical alterations. We do not assume liability for errors in printing or typeing.

Equipment comparison

Type	MIXdrive 6	MIXdrive 15	MIXdrive 60
Stirring points	6	15	60
Stirring point distance	130 mm	65 mm	32.5 mm
Stirring volume / stirring point	1 - 3,000 ml		1 - 500 ml
Stirring power (max.)	40 W		
Material housing	Stainless steel		
Permitted operation conditions Basic-version	-10 up to +50 °C in air, up to +50 °C in water submerged		
Permitted operation conditions HT-version	up to +200 °C in air, up to +95 °C in water submerged		
Operating voltage (max.)	48 VDC		
Dimensions (WxDxH)	245 x 375 x 38 mm		
Protection category	IP68		
Weight (gross)	approx. 9.4 kg	approx. 9.5 kg	approx. 8.9 kg
Order no. Basic-version	40006	40015	40060
Order no. HT-version	40206	40215	40260

Individual units and dimensions on request.
 3 years warranty on material and manufacturing.
 We reserve the right to make technical alterations. We do not assume liability for errors in printing or typeing.

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Россия (495)268-04-70

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Казахстан (772)734-952-31

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

www.2mag.nt-rt.ru | | mge@nt-rt.ru